



SKU : 162508

This series of table and column drilling machines is ideal for light drilling work in steel, cast iron and non-ferrous metals. They are used in workshops and industry for repairs and individual production.

- Universal use
- Compact and powerful
- Robust
- Low maintenance and quiet operation



TECHNICAL SPECS

WORKING AREA

| | |
|--|---------------|
| Drilling capacity | 1.26 in |
| Column diameter | 4 in |
| Quill stroke | 5 in |
| Throat | 9 in |
| Spindle nose-to-table surface distance | 30 in |
| Spindle nose-to-foot distance | 38 in |
| Foot set up area (length x width) | 12 in |
| Table set up area | 13 in x 15 in |

HEADSTOCK

| | |
|---------------|--------------------|
| Spindle mount | 3 MT |
| Spindle speed | 160 rpm - 1880 rpm |

DRIVE CAPACITY

| | |
|-------------------------|------|
| Motor rating main drive | 2 Hp |
|-------------------------|------|

MEASURES AND WEIGHTS

| | |
|--------|---------|
| Height | 69 in |
| Weight | 418 lbs |



PRODUCT DETAILS

- Coolant system
- Belt drive for low-noise operation, low-maintenance and robust design
- Precision spindle bearing - long life and high accuracy
- Table movement via hand-crank and gear rack
- Adjustable depth stop at the capstan handle
- Long quill stroke with precision guide
- Thick-walled column for maximum rigidity during machining of large parts



STANDARD EQUIPMENT

Drill chuck with key
 Tool-holder bits
 Drift bolt
 Coolant system
 Operating tools
 Operator instructions