



Conventional Horizontal Lathes

V-Turn 410 PRO



SKU : 300822

The newly designed PRO models of our bestseller V-Turn convince with improved ergonomics and more safety. Equipped with an inverter and a high-performance spindle motor, they can easily reach 3,000 revolutions per minute. Workpieces with a small diameter can thus be efficiently machined. However, the models also offer strength and stability for heavier machining. The built-in function of the constant cutting speed, which adapts the spindle speed to the diameter when facing, enables turning results that are comparable to CNC machines to be achieved.

- Ergonomic machine housing
- Improved apron with automated feed
- Constant cutting speed
- High spindle speed and motor power
- Roller bearings from world-leading manufacturer NSK

TECHNICAL SPECS

WORKING AREA

Center width	39.37 in
Center height	8 in
Turning diameter over bed	15 in
Turning diameter over gap bridge	23 in
Turning-Ø over support	10 in
Gap bridge length	10 in
Bed width	10 in

TRAVELS

Travel X-axis	8.3 in
Travel Z1-axis	6 in
Swing range of top slide	± 45°

HEADSTOCK

Speed range, high	550 rpm - 3000 rpm
Speed range, low	30 rpm - 550 rpm
Spindle bore	2 in
Spindle mount	Camlock D1-6
Spindle taper	6 MT

FEED

Feed X-axis	0.00051 in/R - 0.01772 in/R
Feed Z-axis	0.00102 in/R - 0.03543 in/R

THREADING

Threading, metric	(39) 02-14 mm
Threading, diametric	(21) 8-44 DP
Threading, module	0.3 mm - 3.5 mm
Threading, whitworth	(45) 2-72 TPI

TAILSTOCK

Tailstock quill diameter	2 in
Tailstock taper	4 MT
Tailstock quill stroke	5 in
Tailstock traverse adjustment	± 0,51 in

DRIVE CAPACITY

Motor rating main drive	7.4 Hp
-------------------------	--------

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	77 in x 40 in x 63 in
Weight	2662 lbs



Extensive accessories, including quick-change tool holder system



Central lubrication is integrated into the support for easy maintenance and handling



PRODUCT DETAILS

- Incl. 3-axis position indicator with integrated spindle speed display, fully assembled
- The redesigned machine enclosure and added safety features make this machine even more ergonomic, complementing functionality and design
- Constant cutting speed: during face turning, the spindle speed automatically adapts to the changing workpiece diameter – the constant cutting speed at the cutting edge of the turning tool ensures superior turning results with quality comparable to CNC lathes
- A heavily ribbed machine bed, rigid headstock and a massive one-piece cast-iron stand form a solid machine base
- Wide, induction-hardened guideways ensure superior turning results and long life
- Facing and top slides feature adjustable guideways and spindle nuts
- High-precision pre-loaded spindle bearings ensure superior concentricity and load capacity
- A powerful 7.4 HP main spindle motor ensures rapid acceleration and powerful chip removal across the entire speed range
- Back-gearing ensures high torque for highly efficient machining
- Rugged feed switch at the support simplifies operation
- The extensive features of the X.Pos Position Indicator are complemented here with a digital speed indicator and an easy to program auxiliary function
- The electromagnetic brake on the main spindle is maintenance-free and slows the machine safely and reliably

CONTROLS & SOFTWARE

3-axis position indicator, X.pos 3.2 VC

- Integrating multiple functions, this new generation of 3 axis digital readouts significantly offer a much better control over the machining processes, greatly decreasing down-times and error rates
- Integrating multiple functions, this new generation of 3 axis digital readouts significantly offer a much better control over the machining processes, greatly decreasing down-times and error rates
- It features a totally sealed enclosure made of high quality polyester film which protects it against hazardous environments in shop floors, such as dust or fumes and offers excellent chemical resistance to most commonly used industry solvents
- Optical Scales: 5 µm resolution (0.000197") with outside cover from aluminum for protection against oil, coolant and chips

Basic Functions

- Resolution of 0.000197"
- Spindle control ON/OFF
- Unit measurement conversion Inch / Metric
- Setting / Resetting current position
- Coordinate display switching ABS / INC
- Radius / Diameter display
- Z1/Z2 Axes summing
- Pocket calculator functions

Extended Functions

- Axis position is maintained when display is turned off
- Hole circle pattern calculation
- Radius / diameter toggle
- Reference function for tool gauging
- Taper turning function

Constant cutting speed

- Allows you to have constant cutting speed during - the spindle speed automatically adjusts based on the turning diameter

STANDARD EQUIPMENT

3-axis position indicator, X.pos 3.2 VC
 4-jaw face plate chuck Ø 10 inch
 Face plate (13" diam.)
 Quick-change tool holder head WB
 Quick change tool holder WBD 25120
 Coolant system
 Steady rest
 Chip tray
 Fixed splash guard (wall)
 Traveling cover for the toolpost
 Follow rest
 Turret stop
 Micrometer stop
 Foot brake pedal
 Chuck guard
 Work light
 Toolbox with operating tools
 Dead center
 Reducing Sleeve
 Operator instructions
 Fixed safety cover made of stainless steel for feed shaft and leadscrew