

Conventional Horizontal Lathes

Turnado 280/2000

SKU : 320560

The machines of the Turnado series are the modern version of the classic lathe. They are characterized by robust construction, a powerful motor and high level of versatility. With the extensive range of standard accessories and options, these machines can be adapted to many production requirements. A modern position indicator is also part of the standard equipment, as is a high-quality quick-change toolholder system. The models in this series have proven themselves many times and have been one of our best-selling conventional lathes for more than 20 years.

- Classic design with sturdy construction
- One-piece heavy casted bed for increased rigidity
- 3-axis position indicator with various turning functions
- Adjustable feed stoppers for longitudinal feed
- Extensive standard equipment package



TECHNICAL SPECS

WORKING AREA

Workpiece length (max.)	76 in
Turning-Ø over bed	22 in
Turning-Ø over support	14 in
Turning diameter over gap bridge	31 in
Gap bridge length	7 in
Bed width	14 in
Center height	11 in

DETAILS

Equipment	with position indicator
-----------	-------------------------

TRAVELS

Travel X-axis	12.4 in
Travel Z1-axis	5 in
Swing range of top slide	± 52°

HEADSTOCK

Spindle speeds	(12) 25 - 1,600 rpm
Spindle bore	3.1 in
Spindle mount	Camlock D1-8
Spindle taper	7 MT

FEED

Feed X-axis	0.00079 in/R - 0.02256 in/R
Feed Z-axis	0.00232 in/R - 0.0648 in/R

THREADING

Threading, metric	0.2 mm - 14 mm
Threading, diametric	(50) 4-112 DP
Threading, module	0.1 mm - 7 mm
Threading, whitworth	(60) 2-112 TPI

TAILSTOCK

Tailstock quill diameter	3 in
Tailstock taper	5 MT
Tailstock quill stroke	7 in
Tailstock traverse adjustment	± 0,47 in

DRIVE CAPACITY

Motor rating main drive	7.4 Hp
-------------------------	--------

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	132 in x 46 in x 58 in
Weight	5984 lbs



PRODUCT DETAILS

- The Turnado Series Universal Lathes are widely tested and proven and our definite bestsellers with a low price and lasting high value

Machine bed

- A heavily ribbed machine bed, rigid headstock and a massive one-piece cast-iron stand form a solid machine base clamping feature for efficient machining
- Removable bridge allows machining of short workpieces with large diameters
- Guideways feature a v-block design and are hardened and ground for lasting precision

Headstock/ feed gear

- The powerful main motor with stepped gears provides high torque and wide range of spindle speeds
- All gears and shafts are hardened and ground and run in an enclosed oil bath
- The large spindle capacity allows clamping of shafts and tubes with large diameters
- The high quality spindle support features optimum rigidity and preloading for high precision even under high radial and axial loads as well as long lasting performance
- A 3-jaw lathe chuck with hard reversible jaws, a 4-jaw independent chuck, and a face plate with large diameter are included in the machine's standard equipment
- The user-friendly control panel at the headstock facilitates rapid user familiarization and intuitive operation
- The feed gear offers a large number of thread leads for metric and Withworth tapping

Support

- The support is designed extra-wide and can easily handle high machining forces
- The control lever for the feed switch and apron nut are designed for user safety with automatic safety interlocking
- The stop spindle features four adjustable cams to provide automatic linear feed shut-off
- This way, repetitive machining processes with different Z axis positions can be simplified by presetting the desired positions in the necessary sequence
- The micrometer bed stop can be used to set precise travel distance limits
- The slip coupling for the automatic feed is positioned centrally on the apron for easy adjustments
- The thread gauge and support allow reliable determination of the pitch after an interrupted tapping process, and also simplifies machining of multi-lead threads
- The top slide swivels and has large, easy to read scaling
- The large, swiveling safety cover at the support protects the user and keeps the work space clean
- A central lubrication system at the support supplies all guideways with lubrication and simplifies maintenance

Tailstock

- The tailstock quill is equipped with a robust and easy to read scale
- The long quill stroke allows for complex drilling and centering jobs
- The tailstock can be adjusted laterally for machining of conical shafts

Accessories

- The standard brake pedal is not only practical, but also a safety feature
- A large and sturdy splash guard on the rear of the machine ensures a clean machine environment
- A bright LED light is integrated in the support cover for optimum lighting throughout the work space
- The multi-functional quick-action tool changer system with 4 tool changer cartridges is included in the standard equipment of this series
- A steady and a live rest are a must for long workpieces and also included in the standard package
- The Turnado Lathe is equipped with the latest generation of our position indicators. Ensures high work precision, lower error rate, and increased operator safety
- A coolant system and extensive operating tools complete the equipment package

CONTROLS & SOFTWARE

3-axis position indicator X.Pos 3.2

- Integrating multiple functions, this new generation of 3 axis digital readouts significantly offer a much better control over the machining processes, greatly decreasing down-times and error rates
- Integrating multiple functions, this new generation of 3 axis digital readouts significantly offer a much better control over the machining processes, greatly decreasing down-times and error rates
- It features a totally sealed enclosure made of high quality polyester film which protects it against hazardous environments in shop floors, such as dust or fumes and offers excellent chemical resistance to most commonly used industry solvents
- Optical Scales: 5 µm resolution (0.000197") with outside cover from aluminum for protection against oil, coolant and chips

Basic Functions

- Resolution of 0.000197"
- Spindle control ON/OFF
- Unit measurement conversion Inch / Metric
- Setting / Resetting current position
- Coordinate display switching ABS / INC
- Radius / Diameter display
- Z1/Z2 Axes summing
- Pocket calculator functions

Extended Functions

- Axis position is maintained when display is turned off
- Hole circle pattern calculation
- Radius / diameter toggle
- Reference function for tool gauging
- Taper turning function

Constant cutting speed

- Allows you to have constant cutting speed during - the spindle speed automatically adjusts based on the turning diameter

STANDARD EQUIPMENT

3-axis position indicator X.Pos 3.2
 Quick tool changer head WC
 Quick change tool holder WCD 32150
 Adjustable feed stops
 3-jaw chuck Ø 12 inch
 4-jaw face chuck Ø 14 inch
 Face plate Ø 17.7 inch
 Follow and steady rests
 Coolant system
 Micrometer longitudinal stop
 Thread gauge
 Reducing sleeve
 Dead center
 Protective shield for the toolpost
 Chuck guard
 Foot brake pedal
 Fixed splash guard (wall)
 Work light
 Toolbox with operating tools
 Operator instructions